



Babak Dizangian

BSc, MSc and PhD: University of Sistan and Baluchestan

Articles:

Year	IF	Journal name	authors	Title	ردیف
2018	1.5	Frontiers of Structural and Civil Engineering	Mohammad Reza Ghasemi Charles V. Camp Babak Dizangian	Novel decoupled framework for reliability-based design optimization of structures using a robust shifting technique	1-1
2018	1.5	Frontiers of Structural and Civil Engineering	Salar, M; Ghasemi, MR; Dizangian, B.	Practical optimization of deployable and scissor-like structures using a fast GA method	1
2018	1.5	Frontiers of Structural and Civil Engineering	Dizangian, Babak; Ghasemi, Mohammad Reza	Border-search and jump reduction method for size optimization of spatial truss structures	2
2016	3.2	steel and composite structures	Dizangian, Babak; Ghasemi, Mohammad Reza;	An Efficient method for Reliable Optimum Design of Trusses	3
2015	علمی پژوهشی	International Journal of Optimization in Civil Engineering	Salar, Masoud; Ghasemi, Mohammad Reza; Dizangian, Babak;	A Fast Ga-Based Method for Solving Truss Optimization Problems	4
2010	علمی پژوهشی	Asian Journal of Civil Engineering (Building and Housing)	Mohammad Reza Ghasemi Babak Dizangian,	Size, Shape and Topology Optimization of Composite Steel Box Girders Using PSO Method	5
2015	ISI, IF= 2.75	Journal of Mechanical Design - Transactions of the ASME	Babak Dizangian, Mohammad Reza Ghasemi	Ranked-based sensitivity analysis for size optimization of structures	6

2015	ISI, IF= 1.57	Journal of the Brazilian Society of Mechanical Sciences and Engineering	Babak Dizangian, Mohammad Reza Ghasemi	A fast decoupled reliability-based design optimization of structures using B-spline interpolation curves	7
2015	Scopus	Asian Journal of Civil Engineering (Building and Housing)	Babak Dizangian, Mohammad Reza Ghasemi	A Fast Marginal Feasibility Search Method in Size Optimization of Truss Structures	8
2015	Scopus	International Journal of Optimization in Civil Engineering	Babak Dizangian, Mohammad Reza Ghasemi	Reliability-Based Design Optimization of Complex Functions Using Self-Adaptive Particle Swarm Optimization Method	9

Conferences and seminars

Year	Conference name	authors	Title	ردیف
	19th international conference on civil and building engineering	Babak Dizangian, Mohammad Reza Ghasemi, Akram Ghalandari	Enhancing Seismic Performance of Ductile Moment Frames with Delayed Wire-Rope Bracing Using Middle Steel Plate	1
	International Conference on Civil Engineering, Architecture and Urban development of Contemporary Iran, Tehran, Iran	Dizangian, Babak; Shahri, Meysam	Comparative Comparison of Contemporary Views of Zahedan City with the City Aesthetic Approach (Case Study of Zahedan University Street)	2
2018	Conference on Civil Engineering, Architecture And Urban Development of The Islamic Countries	Masoud Salar, Babak Dizangian, Morteza Mir	Optimum design of space trusses using water cycle algorithm	3
2017	13th International Conference on Industrial Engineering (IIEC 2017)	Babak Dizangian, Mohammad Mazhari	Surveying the performance of four meta-heuristic optimization algorithm in weight optimization of truss structures	4
2017	13th International Conference on Industrial Engineering (IIEC 2017)	Babak Dizangian, Ali Hooshyari	Comparing the particle swarm, whale, water cycle, and cuckoo search algorithms in optimization of unconstrained problems	5
۱۳۹۶	دومین کنفرانس بین المللی مهندسی عمران، معماری و مدیریت بحران	بابک دیزنگیان، عبدالستار تقوی	بررسی عملکرد المان های زانویی شکل پذیر در سیستم بادبندی چند طبقه ساختمان های بلند دارای قاب های محیطی در مقابل زلزله	6
۱۳۹۶	اولین کنفرانس ملی رویکردهای نو در مهندسی عمران، معماری و شهرسازی	محمدهادی یزدان پناه، بابک دیزنگیان، امیر بهشاد	مکان یابی بهینه المان های مقاوم لرزه ای، جهت بهبود عملکرد لرزه ای ساختمان ها	7
۱۳۸۸	اولین کنفرانس ملی مهندسی و مدیریت زیرساختها پوستر	محمدرضا قاسمی، بابک دیزنگیان	بهینه سازی تیر جعبه ای فلزی و تاوه بتنی در پل ها بوسیله الگوریتم اجتماع مورچگان	8
۱۳۸۹	کنفرانس بین المللی سبک سازی و زلزله ۱ تا ۲ اردیبهشت ۱۳۸۹، جهاد دانشگاهی استان کرمان، بصورت شفاهی	محمدرضا قاسمی، بابک دیزنگیان	سبک سازی عرشه دو عنصری در پلها شامل سیستم مرکب دال بتنی و تیر جعبه ای فلزی بروش ACO	9

۱۳۸۹	کنفرانس ملی صنعتی سازی سازه ها ، تهران- ۱۰ مهر ماه ۱۳۸۹، دانشگاه صنعت آب و برق ارائه شفاهی	بهروز کشته‌گر، بابک دیزنیگان، محمود لایق رفعت	نقش صنعتی سازی بر احتمال خرابی تیر فلزی چند دهانه	10
۱۳۸۹	کنفرانس ملی صنعتی سازی سازه ها ، تهران- ۱۰ مهر ماه ۱۳۸۹، دانشگاه صنعت آب و برق ارائه شفاهی	بهروز کشته‌گر، بابک دیزنیگان، عظیم قلی نژاد	اثر خوردگی بر احتمال خرابی تیر های بتن مسلح	11
۱۳۸۹	پنجمین کنگره ملی مهندسی عمران در مشهد ارائه شفاهی	محمد رضا قاسمی، بابک دیزنیگان	طرح بهینه ابعاد دال بتنی و تیر جعبه ای فلزی در پل ها توسط الگوریتم اجتماع مورچگان	12
۱۳۹۲	هفتمین کنگره مهندسی عمران ۱۷-۱۸ اردیبهشت ۹۲ زاهدان	غلامرضا عزیزیان، فرید میار نعیمی، بابک دیزنیگان، حسین مهماندوست کتله	تأثیر سختی فونداسیون سد بتنی دو قوسی بر پاسخ دینامیکی بدنه سد	13

Ranked-Based Sensitivity Analysis for Size Optimization of Structures

Babak Dizangian

Department of Civil Engineering,
University of Sistan and Baluchestan,
Zahedan 9816811775, Iran

Mohammad Reza Ghasemi¹

Department of Civil Engineering,
University of Sistan and Baluchestan,
Zahedan 9816745437, Iran
e-mail: mrghasemi@hamoon.usb.ac.ir

This article proposes a novel ranked-based method for size optimization of structures. This method uses violation-based sensitivity analysis and borderline adaptive sliding technique (ViS-BLAST) on the margin of feasible nonfeasible (FNF) design space. ViS-BLAST maybe considered a multiphase optimization technique, where in the first phase, the first arbitrary local optimum is found by few analyses and in the second phase, a sequence of local optimum points is found through jumps and BLASTs until the global optimum is found. In fact, this technique reaches a sensitive margin zone where the global optimum is located, with a small number of analyses, utilizing a space-degradation strategy (SDS). This strategy substantially degrades the high order searching space and then proceeds with the proposed ViS-BLAST search for the optimum design. Its robustness and effectiveness are then defied by some well-known benchmark examples. The ViS-BLAST not only speeds up the optimization procedure but also it ensures nonviolated optimum designs. [DOI: 10.1115/1.4031295]

Keywords: violation-based sensitivity analysis, borderline adaptive sliding technique, size optimization

1 Introduction

Over the last decades, a number of optimization techniques have been developed and used for structural optimization problems [1,2]. They may be generally divided into two categories: (i) gradient-based and (ii) stochastic-based techniques. Since there are some known downsides in the application of gradient-based techniques in structural optimization problems, stochastic-based techniques have expanded popularity in recent years [3]. Genetic algorithms [4–10] and simulated annealing algorithms [11,12] are the most notable stochastic-based optimization techniques used in the solution of engineering problems. They do not require the evaluation of gradients of objective and constraint functions, but they involve a substantial extent of computational efforts.

More recently, another branch of nature-inspired algorithms has attracted the attention of researchers in all optimization fields including those addressing structural problems. Algorithms belonging to this field imitate the collective behavior of a group of social insects (for example, bees, termites, ants, and wasps) to solve complex engineering problems (e.g., Refs. [13–20]). These algorithms have become vastly popular. One of the reasons for such popularity is that these metaheuristic algorithms are simple and easy to implement and yet they can solve very diverse and often highly nonlinear problems. They are being progressively enhanced and recognized by researchers for many different studies of structural optimization. However, there is no guarantee that a specific algorithm could perform the best solution for all structural optimization problems [21]. In all nature-inspired methods, the optimization procedure starts from fully random design points and a number of individuals called agents have the duty of finding a better solution by means of time-consuming step-by-step iterations. However, the main problem arises as the number of design variables increases, and thus rising number of agents may be inevitable. For instance, in the first iterations after nature-inspired algorithms begin operations, a large number of analyzes may take

place without an output contentment. This thread is very serious for the structural problems whose analysis is time-consuming. Another insufficiency of such methods is that a large number of parameters should be tuned for every type of problem with a considerable parameter setting.

In this paper, a new method based on ViS-BLAST is proposed to overcome most of the deficiencies of other methods used in structural optimization. The key concept in ViS-BLAST is based on the ranked-based sensitivity analysis that is computed near the FNF border. ViS-BLAST is defined as a two-phase technique. First, using a few number of analyses, it computes the initial local optimum. In the second phase, the sequence of optimum solutions is searched via Jump and BLAST concepts, leading finally to the global optimum. Finally, to demonstrate the capabilities of ViS-BLAST, some well-known benchmark truss problems were solved. Results illustrate the advancements of ViS-BLAST in the fact that it finds *feasible* optimum solutions for all problems attempted, a major point not being specifically emphasized upon by many researchers. Another fact about the proposed method is that it then requires relatively a significant low computational effort to determine the global optimum solution. Although only structural size optimization is considered here, the proposed technique may also be used for problems with shape, topology, and/or hybrid types of design variables.

2 Size Optimization Formulation

Size optimization of structural systems involves reaching optimum values for design variables as member cross-sectional areas A that minimize the objective function f , usually the structural weight W . This is expressed mathematically as

$$\text{Minimize } f = W(\mathbf{A}) = \sum_{j=1}^n A_j L_j \rho_j \quad (1)$$

where A_j , L_j , and ρ_j are the cross-sectional area, length, and unit weight of the j th member, respectively, and n is the total number of members. The vector \mathbf{A} is selected between lower A^L and upper A^U bounds. Equation (1) is subjected to the following normalized constraints:

¹Corresponding author.

Contributed by the Design Automation Committee of ASME for publication in the JOURNAL OF MECHANICAL DESIGN. Manuscript received January 13, 2015; final manuscript received August 6, 2015; published online October 16, 2015. Assoc. Editor: Nam H. Kim.



A fast decoupled reliability-based design optimization of structures using B-spline interpolation curves

Babak Dizangian¹ · Mohammad Reza Ghasemi¹

Received: 31 January 2015 / Accepted: 1 September 2015 / Published online: 15 September 2015
 © The Brazilian Society of Mechanical Sciences and Engineering 2015

Abstract This paper introduces a new method for reliability-based design optimization (RBDO) of structures. In RBDO of structural problems unlike the conventional two-level approaches, sometimes it is not necessary to carry out reliability analysis for each deterministic design. The proposed method may be categorized as a decoupled method for reliable optimum design; however, it is based on the safety factor (SF) concept. To briefly describe the proposed method, a deterministic design optimization (DDO) point is obtained based on an arbitrary SF. The corresponding failure probability (P_f) is then determined using Monte Carlo simulation (MCS). The P_f is then compared with the targeted P_f . If the relative distance error is greater than a desirable tolerance, the cubic B-spline interpolation concept is then employed as a result of which a modified SF is extracted. For the modified SF found, DDO procedure is carried out. The above procedure is iteratively repeated until convergence occurs and the reliable optimum point is found. Finally, the proposed method was applied to solving some structural problems. The obtained results were favourably in accordance with those recorded in the literature while only a fraction of P_f computations was necessary.

Keywords Decoupled · Reliability · Optimization · Structural · B-spline · Interpolation

Technical Editor: Marcelo A. Trindade.

✉ Mohammad Reza Ghasemi
 mrghasemi@hamoon.usb.ac.ir

¹ Department of Civil Engineering, University of Sistan and Baluchestan, Zahedan, Iran

1 Introduction

Reliability-based design optimization (RBDO) implements structural optimization considering simultaneously the uncertainties in the structural materials properties and/or applied loading. The general structural RBDO problem with both deterministic and probabilistic design constraints can be expressed as:

Min/Max $f(\mathbf{d})$

Subject to:

$$\begin{aligned}
 P(G_i(\mathbf{d}, \mathbf{X}) \leq 0) &\leq P_f^i, \quad i = 1, \dots, N_{PC} \\
 \text{and/or } \sigma_j(\mathbf{d}) &\leq \sigma_{\text{all}}, \quad j = 1, \dots, N_m \\
 \text{and/or } u_k(\mathbf{d}) &\leq u_{\text{all}}, \quad k = 1, \dots, N_{DOF} \\
 \text{and/or } \mathbf{d}^L &\leq \mathbf{d} \leq \mathbf{d}^U
 \end{aligned} \tag{1}$$

where $\mathbf{d} = [d_1, d_2, \dots, d_n]^T$ is a column vector of n deterministic design variables, $\mathbf{X} = [x_1, x_2, \dots, x_m]^T$ is the m -dimensional vector of random variables, $f(\mathbf{d})$ is the objective function, $P(G_i(\mathbf{d}, \mathbf{X}) \leq 0)$ denotes the failure probability for the i -th limit state function $G_i(\mathbf{d}, \mathbf{X})$. P_f^i is the target failure probability of i -th constraint and N_{PC} is the number of probabilistic constraints. In Eq. (1), σ and u are the stress of j th member and the nodal displacement of k -th degree of freedom, respectively. σ_{all} , u_{all} , \mathbf{d}^L , \mathbf{d}^U , N_m and N_{DOF} are respectively allowable member stress, allowable nodal displacement, lower and upper bounds of \mathbf{d} , total number of members of the structure and total number of degrees-of-freedom. The target failure probability can be expressed in terms of the target reliability index, $P_f^i = \Phi(-\beta_{ti})$, as $\Phi(\cdot)$ is the standard normal cumulative distribution function.